WHY CHOOSE **FREEZY** CONDENSATE PUMPS






FEATURES & BENEFITS

The FREEZY is equipped with revolutionary high-performance, field-specific technology; a non-contact fluid-detection sensor. The non-contact fluid-detection sensor avoids leak paths, material contamination, offers high-moisture resistance, fast response time (32 μ seconds) and can easily replace any conventional electro-mechanical switch and digital sensor.

- Sleek and versatile installation -Can be installed on the bottom left or right-hand side of any unit, and color matched to all evaporators ensuring the highest level of functionality without affecting aesthetics
- Universal and *virtually maintenance-free - A slim, simple design allows it to be used with any brand of ductless evaporator
- Smoke & flame resistant
 Body made with the most flame retardant, UL94-5VA certified material
- 2 Year Warranty**

- IP65 Certifed with PCB isolated & protected from moisture and any water intrusion
- With the revolutionary non-contact fluid-detection sensor, this unit:
 - Avoids leak paths
 - Avoids material contamination
 - Offers high-moisture resistance
 - Fast response time (32 μ sec)
 - Can easily replace any conventional electro-mechanical switch and digital sensor



QUICK REFERENCE GUIDE			
Part Number	FREEZY		
Max Flow Rate	5.3 GPH		
Max Head	28′		
Sound	<19 dB		
Voltage	110 OR 240V 50/60 HZ		
Alarm Relay	NO/NC 8A 110-240VAC		
Discharge Tube	1/4″ ID		
Color	WHITE		
Thermal Protection	UP TO 212°F		
Installation Range	6,000-54,000 BTU/H		
Dimensions (H/W/L)	1.9 x 2.5 x 10.15″		



Engineered, manufactured and tested according to rigid Swiss quality standards. Product certifications available upon request.

* Extremely low maintenence. **Two (2) years for manufacturing defects only.

SUBMITTAL DATA SHEET CONDENSATE PUMPS					
Job Name	Location				
Purchaser	Engineer				
Submitted To	Reference	Approval	Construction		
Submitted By					
Unit Designation	Schedule				
Construction	Date				
